0. 1.151	
Standard Plan	ES-6A, ES-6B, ES-6C, ES-6D, ES-6E, ES-6F, ES-6G
Numbers	ES-7A, ES-7B, ES-7C, ES-7D, ES-7E, ES-7F, ES-7G, ES-7H, ES-7J, ES-7K, ES-7L,
	ES-7M, ES-7N, ES-7O, ES-7P, ES-7Q, ES-7R
	ES-11
	ES-16A, ES-16B, ES-16C, ES-16D
	Note that ES-14C deals with an overhead sign structure and is not covered by
	this user guide.
Implementation	This user guide applies to the latest versions of Standard Plan Numbers above.
Description of	Used for structural supports for
Component	
•	 luminaires
	• signals
	flashing beacons
	CCTV
	Vehicle detection system (VDS)
	street name signs
	 push button assemblies and accessible pedestrian signals
	 certain other miscellaneous items.
	Also used for guard posts and pedestrian barricades
	Use inside or outside of Special Wind Regions. Use inside or outside of Ice
	Regions.
Standard Plan	The ES-6 Series include various structural supports for luminaires.
Features	
	ES-7A through ES-7L includes various structural supports for
	Traffic Signals
	Pedestrian Signals
	Street Name Signs
	• Luminaires
	Push Button Assemblies
	Accessible Pedestrian Signals
	Flashing Beacons
	Certain associated sign panels
	FC 7M through FC 7O includes unuique granted dataile and mater that a self-trail
	ES-7M through ES-7O includes various general details and notes that apply to
	the ES-6 and ES-7 series.

Standard Plan	ES-7P includes detailing for Internally Illuminated Street Name Signs
Features (continued)	ES-7Q includes guard posts and pedestrian barricades
(commuta)	
	ES-7R includes details for miscellaneous attachments to structural supports for luminaires and traffic signals conforming to 2010 and later Standard Plans. Use
	of these details to attaching items to older supports and nonstandard supports
	should consider the ability of the structure to support the changes.
	ES-11 Includes additional foundation information that applies to most
	structures covered by this User Guide.
	ES-16A through ES-16C covers structural supports for CCTV systems.
	ES-16D covers structural supports for CCTV with VDS systems. Note that this
	sheet was intended to provide some flexibility for mounting of a variety of attachments within parameters given on the sheet.
Project	Check for latest applicable version of Standard Plan(s) and SSP from
Development	http://www.dot.ca.gov/des/oe/construction-contract-standards.html
Procedures	Get the applicable version of this User Guide from
	http://des.onramp.dot.ca.gov/structure-policy-innovation/signs-
	<u>overhead-structures</u>
	Check for other documents that might apply. Some examples are:
	Ramp Metering Design Manual
	o California MUTCD
	o Traffic Manual
	 Verify that the project conforms to Standard Plans, this User Guide, the specifications, and other requirements and determine which sheets are needed.
	 For questions on interpretation of the Standard Plans or the User Guide, contact the Senior Technical Specialist for Signs and Overhead Structures.
	 For questions on the interpretation of the structural information in the Standard Specifications and Standard Special Provisions contact the Office of Structure Specification Research and Development.
	If elements of the project do not conform, then a special design is needed.

Design/General	
Notes	Structural Design Notes:
	Design Specification:
	 AASHTO Standard Specifications for Structural Supports for
	Highway Signs, Luminaires, and Traffic Signals, Sixth Edition
	(LTS-6) dated 2013.
	GROUP LOAD COMBINATIONS:
	o I Dead Load
	 II Dead Load + Wind Load
	 III Dead Load + 0.5 (Wind Load) + Ice Load
	o IV Fatigue Load
	LOADING:
	 Wind Loading:
	■ 100 mph (3-second gust)
	 Combined height, exposure, and elevated terrain
	factor = 1.00
	■ Importance factor, Ir = 1.00 (50 year recurrence
	interval)
	o Ice Loading:
	 3.0 psf on surfaces, 0.60 in radial thickness of ice
	o Fatigue: LTS-6, Section 11
	 Galloping,
	■ Natural Wind Gust,
	■ Truck-Induced Gust
	Yearly Mean Wind Velocity (15.6 mph)
	■ Fatigue Importance factor, I _F = 1.0
	MATERIAL PROPERTIES:
	Structural Steel: -
	• f _y = 55,000 psi (tapered steel tubes and anchor bolts)
	 Other plates, bars, hot rolled open shapes, f_y = 50,000
	psi Wold Filler Metal F = 70 000 psi
	 Weld Filler Metal, F_u = 70,000 psi Anchor Bolts: ASTM F1554 Grade 55
	HS Anchor Bolts for Slip Bases: ASTM F1554 Grade 105
	HS Cap Screws: ASTM A325
	Reinforced Concrete:
	■ f′ _c = 3,600 psi
	• f _y = 60,000 psi
	,, 55,555 ps.
	I .

Foundation Design	 CIDH Foundation Design (Broms' Method in LTS-6 Section 13): Overload Factor = 2 Undercapacity Factor = 0.7 Cohesionless Soil Method Soil unit weight, λ= 120 pcf Friction angle, φ= 30° Cohesive Soil Method Shear strength, c = 1500 psf CIDH length was also checked for torsion resistance following the Florida Department of Transportation (FDOT) modifications to section 13.6.1.1 of LTS-6 Friction coefficient between shaft and soil, μ = 0.3
Additional	Roadway and Electrical plans showing various other related info.
Drawings Needed to Complete PS&E	Special designs where needed.
Contract	Standard Specifications.
Specifications	Revised Standard Specifications
	Standard Special Provision (SSP) from
	http://www.dot.ca.gov/des/oe/construction-contract-standards.html
Restrictions on Use of Standard Drawings	If project conditions require significant deviations from these standards, the design might require a special design. Some examples might be:
	Additional loads not shown
	Additional holes or welding not shown
	Deviations from dimensions (but see Other User Options below)
	 Soils not meeting minimum properties shown in "Foundation Design"
	 Locations where finish grade at base of standards is more than 33' above surrounding terrain
Other User Options	For traffic signal structures on ES-7C, ES-7D, ES-7E, ES-7F, ES-7G, and
Callet Osci Options	ES-7H that include a luminaire mast arm, the luminaire mast arm may be oriented in a plan direction other than parallel with the signal mast arm. Include information in contract documents to clearly indicate which structures will have a different luminaire mast arm direction and what the direction is to be.